




Happy D.2 Wall-mounted toilet # 222209..00 / 222209..00 / 222209..00

| < 365 mm > |



Wall-mounted toilet	Dimension	Weight	Order number
Washdown model, Rimless, Flush principle: ousting, Outlet drain horizontal, Unified Water Label (UWL) Class: 1			
Colors			
00 White High Gloss 20 White High Gloss, HygieneGlaze AD Anthracite Matt, DuraShield			
Variant			
♣ White High Gloss, Flush water quantity: 3 l, Fixing included: Durafix	365x540 mm	24.700 kg	222209..00
♣ White High Gloss, HygieneGlaze, Flush water quantity: 4,5/3 l, Fixing included: Durafix	365x540 mm	24.700 kg	222209..00
♣ Anthracite Matt, DuraShield, Flush water quantity: 4,5/3 l, Fixing included: Durafix	365x540 mm	24.700 kg	222209..00
Accessory for ceramics for White High Gloss, Flush water quantity: 3 l, Fixing included: Durafix			
Fixation Suitable for Wall-mounted bidet, Wall-mounted toilet	180 x 42 mm	0.28 kg	006500
Accessory			
Noise reduction set	420 x 390 mm	0.2 kg	005090
Suitable products			
Toilet seat Shape: Rectangular, Soft-closing: Yes, Removable Seat, Hinge material: Stainless steel, 359 x 430 mm	359 x 430 mm		006459
Installation element dry installation for toilet Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm	155 x 500 mm		WD1011

Happy D.2 Wall-mounted toilet # 222209..00 / 222209..00 / 222209..00

| < 365 mm > |

<p>Installation element dry installation for toilet Hygienic flush, 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Electronic, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1013
<p>Installation element dry installation for toilet Odor extraction, Fan activation: Automatic, Manual, At the touch of a button, Touchless, Hygienic flush, 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Electronic, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1014
<p>Installation element wet installation for toilet Type of installation: For walling in and out, Type of mounting: Wet installation, Max. projection toilet: 700 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, 153 x 445 mm</p>	153 x 445 mm	WD1015
<p>Installation element dry installation for toilet Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1016
<p>Installation element dry installation for toilet Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1017
<p>Installation element dry installation for toilet Standard 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1018

Happy D.2 Wall-mounted toilet # 222209..00 / 222209..00 / 222209..00

|< 365 mm >|

<p>Installation element dry installation for toilet Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: FrontTop, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1019
<p>Installation element dry installation for toilet Basic 6 l, Powder-coated, Type of installation: In standard lightweight construction, In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Mechanical, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Throttle for regulating the flush flow, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 155 x 500 mm</p>	155 x 500 mm	WD1020
<p>Installation element dry installation for toilet Hygienic flush, 6 l, Powder-coated, Type of installation: In front of solid wall, Type of mounting: Drywall, Max. projection toilet: 625 mm, Height adjustable: 240 mm, Flush operation: Electronic, Flush operation position: Front, Adjustable flush volumes, Flush type: Dual Flush, insulated against condensation, Self-supporting, Suitable for panelling with plasterboards, Small flushing volume: 3 l, Large flushing volume: 6 l, 90 x 590 mm</p>	90 x 590 mm	WD1023

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.