

OPCIONES**Volumen de Descarga**

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

Terminar

Blanco Mate

Cromo Pulido

Inoxidable Cepillado

Negro Mate

Eficiencia en el Consumo de Agua

Alta Eficiencia

Bajo Consumo

Cumplimientos y Certificaciones

Cumplen con la Ley ADA

BREEAM Water Credit

Green Globes Water Credit

cUPC Certified (Requires use of listed vacuum breaker that complies with ASSE 1001)

NOTAS

Para dibujos de línea de productos, [ver hojas de especificaciones específicas del modelo](#).

Toda la información contenida dentro de este documento está sujeta a cambio sin previo aviso.



Imagen para un estándar TRF 8156 se muestra

DESCRIPCIÓN

TruFlush Oculta Sensor Sanitario Fluxómetro

CARACTERÍSTICAS

- Fluxómetro verdadero proporciona volumen de agua exacto
- Cuerpo de válvula de latón sin cromo de servicio pesado
- Sensor infrarrojo energizado con baterías proporciona activación sin contacto
- Placa de pared cromada, antivandalismo, con botón de sobrepaso electrónico
- Ensamble de pistón reemplazable, accesible a través de la placa de pared frontal
- Funda de corte oculta ajusta el índice de flujo
- **No disponible en EE UU ni Canadá**
- Cuerpo de válvula, Cubierta, Boquilla y Válvula de Retención cumplirán con la Clasificación de Aleación de ASTM para Latón Semi-Rojo

DESCARGAS

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Descargas Adicionales](#)

VIDEOS

- ▶ [TruFlush](#)
- ▶ [TruFlush Installation](#)
- ▶ [TruFlush Maintenance](#)
- ▶ [TruFlush Flush Line](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Teléfono: 800.982.5839 • Fax: 800.447.8329 • sloan.com



Elongated Wall-Mounted Water Closet

ST-2459

Product description

Standard, Vitreous China Wall-Mounted Water Closet.

Compliances & Certifications



(ADA Compliant, BREEAM Materials Credit, CalGreen Compliant, CEC Compliant, EPD, Green Globes Credit, HPD, LEED Credit, LEED HPD, Satisfies LEED Credits, EPA WaterSense Listed, WELL Building Standard)

Code 2102459

Downloads

- [HET Wall Hung Water Closet Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.1-1.6 gpf (4.2-6 lpf)
- RIM Height: 13.25" -17.00" (337 - 432 mm)
- Nominal Dimensions: 26.75" x 15" x 13.25" (679 x 381 x 337mm)

Features

- Maximum static load rating of 1,000 lbs when installed on an appropriate wall carrier support system (not recommended for bariatric use)
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphon jet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly
- Designed to complement Sloan flushometers

Recommended Seats

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Bemis - BB955CT
- Church - 1580CT
- Church - 295CT/295SSCT & 2155CT/2155SSCT

Plumbing System Requirements

- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

[Find a compatible flushometer](#) for this water closet

WaterSense compliant when used with a WaterSense compliant flushometer.

